

Preliminary Product Specifications

FlashLink. NOW 4G Real-Time In-Transit Logger

Temperature Range	-20°C to 60°C (-4°F to 140°F)
Temperature Accuracy	±0.5°C from -20°C to 60°C (-4°F to 140°F)
Temperature Resolution	0.1°C/°F
Temperature Sensor Type	Internal Digital Temperature Sensor (NIST traceable)
Humidity Range	0% to 100%
Humidity Accuracy	±5%RH @ 25°C
Light Sensor Range	On / Off
Usage Type	Single Use
Data Capacity	Max 27000 readings
Logging Interval	10 Min.
Data Upload Interval	90 Min.
Trip Duration	70 Days
Cellular	LTE CAT-1 with 2G fallback
SIM	Internal Embedded (Global Data Roaming) Nano Sim
Power Source	Non-Lithium Ni-MH
Logger Dimensions	4.2in [with loop: 4.5in] x 2.7in x 0.9in (106.4mm [with loop: 113.8mm] x 68.6mm x 22.3mm)
Weight	TBD
Waterproof Rating	IP54
Certification	FCC, CE, TELEC, ROHS
Protocol	MQTT/MQTTs 3.1.1



Model 23002-02

- Next generation of global cellular communications real-time loggers using 4G LTE with 2G backup
- Precision location accuracy using latest global cellular technology with Wi-Fi triangulation positioning
- Monitors location, temperature, humidity, light
- Proactively manage shipment location and conditions to reduce the risk of product loss due temperature excursions
- FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions
- Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 23002-02_24L1

